



C394 FROZEN CARBONATED BEVERAGE MACHINE

FOUR FLAVOR

FEATURES

Features

Dispense a light, fluffy, high overrun slush product in a pressurized system from this modular, counter-top freezer. Air is discharged out the top of the unit to accommodate tight counter space. Optional cart converts the unit to a self-contained floor model, and provides storage for the syrup.

Freezing Cylinder

Four, 7 quart (6.6 liter).

Improved technology has efficient freeze time and recovery for high demand draws during peak hours.

Dispensing Door

Clear plastic dispensing door and handles attract impulse sales, and visual attraction to product flavors. Self closing draw handles are standard. Round dispensing nozzle conveniently fits the hole in domed lids.

Product Delivery System

Quick change orifices expand flavor options from FCB to fountain syrups for maximum versatility. "Push to connect" fittings allow for quick flavor adaptations to meet customer preferences and seasonal demands.

Indicator Lights/Audible Alarm

Lights flash and audible alarm sounds to indicate loss of CO2, water or syrup on the affected freezing cylinder. The other flavors will continue to operate when one loses syrup. A snooze feature may be activated to silence the alarm for 15 minutes.

Automatic Defrost

Programmable defrost cycles allow the operator to select the time and frequency for defrosting each freezing cylinder independently. The indicator light flashes to warn customers not to draw product from the freezing cylinder that is being defrosted. At the end of the defrost cycle, the freezing cylinder automatically returns to the freeze-down mode.

Power Saver Description

During extended no-use periods, the Power Saver feature may be programmed for Rest Mode. Rest Mode shuts down the refrigeration system for the most energy savings. Start and end times may be programmed independently for seven cycles.

Air Filter

Easily removable, cleanable air filter located in front of unit. Filter helps keep condenser clean for optimal refrigeration system performance.

Merchandising

The light box merchandising feature enhances brand visibility and POS marketing opportunities with vibrant lighting. LED display illuminates translight and clear dispensing doors to draw customer attention. This display provides energy efficient, and consistent lighting.

Innovative Connectivity

Unit is IoT capable. Open Kitchen connectivity enables real-time monitoring of equipment performance from any device, optimizing operations.

SPECIFICATIONS

Weights	lb.	kg
Net	455	206.3
Dimensions	in.	mm
Width	30-5/16	769.5
Depth	35-7/8	910.8
Height	40-3/16	1021

*Designed to rest on a plastic pad directly on counter top or optional cart.

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	25	19	2P 3W
208-230/60/3 Air	20	15	3P 4W



To Contact a Distributor visit: www.taylor-company.com/distributors